

doi: 10.52370/TISC26265MM

HERITAGE 4.0: DIGITAL CONSERVATION, SUSTAINABLE TOURISM AND PROACTIVE CULTURAL SITE MANAGEMENT

Milica Marinković¹

Abstract

This paper aims to develop the "Heritage 4.0" conceptual model, which integrates digital analytics, sensor networks, and human-in-the-loop principles for the proactive management of cultural sites. The research is motivated by the limitations of traditional, reactive conservation methods that intervene only after visible degradation occurs. The study employs systemic modeling, technology analysis, and predictive analytics, utilizing Heritage Remaining Useful Life (HRUL) as a predictive degradation assessment framework. The proposed model enables continuous condition monitoring, simulation-based risk assessment, and preventive intervention planning, while ensuring that final decisions remain within the jurisdiction of experts. Consequently, it provides a methodological framework for enhancing sustainable conservation and strategic visitor management. Furthermore, the model facilitates digital heritage valorization and integration with sustainable tourism, establishing a foundation for future empirical research and practical application in cultural site management.

Key Words: *Heritage 4.0, digital conservation, predictive analytics, sustainable tourism, human-in-the-loop*

JEL classification: Z30, Q01, O33

Introduction

Cultural heritage represents a fundamental component of community identity and a key resource for sustainable tourism. However, it is increasingly threatened by anthropogenic pressures, climate change, and

¹ Milica Marinković, PhD student, Junior Researcher, University of Kragujevac, Faculty of Hotel and Tourism Management, Vrnjačka Banja, Serbia, +38166435280, milicamarinkovic1101@gmail.com

natural degradation. Although traditional conservation approaches remain essential, they are predominantly reactive, as interventions occur only after visible deterioration, often resulting in irreversible loss of value and higher restoration costs.

Recent developments within Industry 4.0, including digital twins, IoT sensor networks, and artificial intelligence, demonstrate significant potential for heritage management. However, an integrated methodological framework that combines predictive conservation with strategic tourism management remains underdeveloped. This gap highlights the need for a proactive approach that ensures both the preservation of cultural assets and the continuity of the visitor experience.

In response to this gap, this paper proposes the “Heritage 4.0” conceptual model. The aim is to develop a systemic framework for proactive cultural site management based on sensor integration and predictive analytics. The model introduces the Heritage Remaining Useful Life (HRUL) framework as a tool for degradation forecasting, risk assessment, and decision support.

Theoretical Framework

Modern cultural heritage management is constrained by the limitations of traditional reactive maintenance models, in which interventions are initiated only after degradation becomes visible or structurally critical. This approach limits systemic risk management and leads to suboptimal allocation of conservation resources. In contrast, principles of minimal intervention and reversibility, as defined in the Venice Charter (ICOMOS, 1964), together with contemporary World Heritage management guidelines (UNESCO, 2023), implicitly support a preventive paradigm based on early risk identification. Ashley-Smith (1999) further argues that the identification and quantification of degradation probability provides a more efficient and ethically sustainable alternative to reactive restoration. Consequently, the transition from static documentation toward dynamic systems of monitoring, analysis, and prediction becomes essential in contemporary heritage practice.

Digital heritage documentation has evolved from 2D recording toward 3D modeling, photogrammetry, and Heritage Building Information Modelling (HBIM) systems (Murphy et al., 2009). HBIM enables the integration of precise geometric data with semantic information related to

materials, historical phases, and conservation interventions. However, these systems remain predominantly static and lack continuous interaction with the physical environment. This limitation is addressed through the digital twin paradigm, which integrates a physical system, a digital representation, and a real-time data stream (Grieves, 2014; Glaessgen & Stargel, 2012). Beyond visualization, its main value lies in continuous state synchronization, simulation capability, and predictive analytics (Tao et al., 2018). In cultural heritage contexts, this concept is extended into the Heritage Digital Twin (HDT), which integrates HBIM, sensor networks, and analytical models into operational tools for monitoring and risk management (Bruno et al., 2010).

The predictive component of the model is based on the Remaining Useful Life (RUL) concept, originally developed in industrial systems as a probabilistic estimate of the time remaining until a failure threshold is reached (Sikorska et al., 2011), formally expressed as:

$$RUL(t) = E[T - t \mid \Delta(t)]$$

where T denotes the time of failure, t the observation time, and $\Delta(t)$ historical condition data. In heritage contexts, failure is redefined as a critical degradation threshold associated with irreversible material, structural, or symbolic loss. Accordingly, within heritage systems, RUL is reinterpreted as a probabilistic estimation of the remaining time before a cultural asset reaches a critical degradation threshold associated with potential irreversible loss.

A key methodological challenge in applying RUL to heritage systems is the “Small Data” problem. Cultural assets are unique, degradation processes are non-linear, and available datasets are limited and heterogeneous. This increases the risk of overfitting in data-driven models; therefore, machine learning approaches rely on transfer learning, local calibration, and expert validation (Bzdok & Ioannidis, 2019; Pan & Yang, 2010). Within this framework, Convolutional Neural Networks (CNNs) are used for visual pattern recognition (LeCun et al., 2015), while Long Short-Term Memory (LSTM) networks support temporal modeling of degradation processes (Hochreiter & Schmidhuber, 1997). Combined with a human-in-the-loop approach, AI functions as decision support, while final responsibility remains with conservation experts.

Methodological Approach and Research Conceptual Framework

The study is grounded in a conceptual-theoretical approach aimed at developing an integrated model for the proactive management of cultural sites. The methodological framework comprises systemic modeling, comparative analysis of industrial and cultural risk management systems, and synthesis of existing theoretical and technological paradigms within the fields of digital twins, HBIM systems, and predictive maintenance.

The foundation of this paper lies in identifying the structural limitations of reactive conservation models, followed by a theoretical reinterpretation of the industrial Remaining Useful Life (RUL) concept within the context of cultural heritage. This reinterpretation involves a normative adaptation of degradation indicators, whereby the technically defined notion of “failure” is translated into a critical degradation threshold encompassing material, historical, and symbolic dimensions of cultural value. The methodological development process is structured in three phases: (1) analysis of existing theoretical frameworks and technological solutions; (2) identification of their limitations within cultural heritage applications; and (3) construction of an integrated conceptual model combining the Heritage Digital Twin, the redefined RUL indicator, and a human-in-the-loop decision framework for sustainable tourism management.

The “Heritage 4.0” model is based on a systemic modeling methodology integrating digital conservation technologies, sensor infrastructures, and AI-based analytics. Its objective is not longitudinal performance certification, as in industrial systems, but methodological structuring, simulation-based risk assessment, and the provision of quantitative support for strategic decision-making. The framework integrates digital twin principles, predictive maintenance logic, and sustainable tourism pressure management into a unified operational system, enabling simultaneous monitoring of structural and environmental conditions.

Data acquisition is performed through a multimodal sensing infrastructure. High-resolution LiDAR scanning generates 3D representations of cultural assets and detects micro-scale structural anomalies, including cracks, deformations, and volumetric changes. IoT sensor networks continuously monitor microclimatic conditions, including temperature, relative humidity, and pollutant concentration levels. These datasets are further complemented by external climate databases to enable comparative temporal analysis and long-term environmental impact assessment.

Sensor fusion is applied to normalize and synchronize heterogeneous geometric, microclimatic, and environmental datasets into a unified analytical repository, forming the basis for AI-based processing. Within the analytical layer, Convolutional Neural Networks (CNN) extract spatial structural features associated with visible degradation, while Long Short-Term Memory (LSTM) networks model temporal dependencies in environmental and structural evolution patterns. CNN-derived outputs primarily inform structural condition variables S , whereas LSTM-based outputs capture temporal dynamics contributing to microclimatic (M) and anthropogenic (A) components.

Heritage Remaining Useful Life (HRUL) is conceptualized as a heritage-adapted reinterpretation of the industrial Remaining Useful Life framework. Unlike conventional industrial RUL models focused on functional system failure, HRUL estimates the expected remaining time before a cultural asset reaches a critical degradation threshold associated with irreversible material, structural, or symbolic loss. Formally, the model is expressed as:

$$H_{RUL}(t) = E[T_c - t | S(t), M(t), A(t)]$$

where T_c denotes the projected time at which the cultural asset reaches the critical degradation threshold, while $S(t)$, $M(t)$, and $A(t)$ represent structural, microclimatic, and anthropogenic variables at time t . Here, t denotes the current observation time at which the state of the system is evaluated.

While HRUL represents a temporal degradation estimation, the model further operationalizes this estimation through a normalized probabilistic risk layer:

$$R_H = g(H_{RUL}) \rightarrow [0, 1]$$

where R_H represents a normalized degradation risk score indicating the probability of transition toward a critical condition state within a defined temporal horizon. The decision logic is governed through predefined intervention thresholds, where the critical threshold (τ_c) is derived through expert calibration and statistical analysis of degradation distributions. When R_H approaches or exceeds τ_c , the system transitions from passive monitoring toward adaptive risk mitigation. In practice, τ_c is calibrated using historical data where available, combined with expert

elicitation and simulation-based tuning. HRUL is obtained by transforming S, M, and A into normalized numerical indices, while data heterogeneity is resolved through preprocessing, temporal alignment, and feature-level fusion prior to model inference.

Operationally, the framework follows a structured loop involving multimodal data acquisition (S, M, A), sensor fusion, AI-based feature extraction, computation of HRUL and RH, comparative evaluation against τ_c , and expert validation within a human-in-the-loop framework. This enables graded intervention strategies, including intensified monitoring, restricted physical access, and adaptive redistribution of visitor flows.


To illustrate the model's operationalization, a hypothetical fresco-sensitive enclosed heritage site is considered. Under baseline conditions, multimodal inputs indicate stable structural and environmental states, with high HRUL values and low RH risk levels well below the intervention threshold τ_c . Under a simulated stress scenario (increased visitor flow +20%, rising humidity, and progressive micro-crack development), structural (S), microclimatic (M), and anthropogenic (A) indicators show deterioration trends. Accordingly, HRUL decreases over time, while RH increases in a non-linear manner. As RH approaches τ_c , the system transitions from a stable to a warning state, demonstrating its role as a predictive early-warning mechanism enabling preventive intervention before irreversible loss.

A central principle of the framework is the human-in-the-loop paradigm, whereby AI-based outputs serve as decision-support tools, while final validation and intervention authority remain with conservation experts in accordance with established ethical and conservation principles. In the tourism domain, the model introduces the concept of digital tourist dispersion. When RH indicates elevated risk conditions, the system recommends reducing physical access and redirecting visitors toward digital alternatives, including virtual reconstructions, immersive environments, and interactive 3D models. This approach reduces anthropogenic pressure on physical sites, extends their functional preservation horizon, and maintains continuity of the visitor experience. Inclusivity is thereby enhanced through improved accessibility for individuals with mobility or sensory limitations, as well as through the reduction of geographical and economic barriers.

The proposed framework is designed for validation through scenario-based simulations and prospective pilot implementations in selected heritage sites, enabling evaluation of system robustness, predictive accuracy, and decision-support effectiveness under controlled and real-world operational conditions.

By integrating predictive conservation mechanisms with sustainable tourism management, the “Heritage 4.0” model establishes a unified framework that transcends purely technical monitoring approaches and strengthens the strategic dimension of heritage governance. Positioned at the intersection of Industry 4.0 and Tourism 4.0 paradigms, the framework contributes to the long-term sustainability and resilience of cultural heritage systems. Figure 1 illustrates the conceptual architecture of the model, highlighting interactions between data acquisition, analytical processing, and adaptive visitor management mechanisms.

Figure 1: *The “Heritage 4.0” Conceptual Model*



Source: *Author*

Discussion

The “Heritage 4.0” model aligns preventive conservation principles, such as minimal intervention and reversibility (ICOMOS, 1964), with contemporary digital transformation frameworks in heritage management (UNESCO, 2023). In doing so, it supports key sustainability objectives,

particularly SDG 9 (Industry, Innovation, and Infrastructure) and SDG 11 (Sustainable Cities and Communities), contributing to a transition from reactive to predictive and adaptive heritage governance.

A central contribution of the model is the HRUL-based predictive framework, which enables probabilistic degradation forecasting and early detection of critical thresholds. Its operational relevance is reinforced through a context-dependent threshold (τ_c) and an explicit decision logic structure, which transforms risk estimation into actionable conservation governance. By integrating structural, environmental, and anthropogenic factors, the model conceptualizes heritage degradation as a dynamic, multi-dimensional process supported by continuous sensor data, predictive analytics, and human-in-the-loop expert oversight.

Compared to static HBIM and earlier digital twin approaches, the framework introduces continuous data integration and a structured decision loop (data acquisition $\rightarrow$ fusion $\rightarrow$ AI processing $\rightarrow$ HRUL estimation $\rightarrow$ τ_c evaluation $\rightarrow$ expert validation), improving early anomaly detection and enabling adaptive conservation strategies (Murphy et al., 2009; Grieves, 2014). Overall, Heritage 4.0 integrates conservation, risk prediction, and tourism management into a unified adaptive governance framework, positioning heritage as a continuously evolving system rather than a static object.

Conclusion

The “Heritage 4.0” model represents a conceptual framework that integrates technological innovation, conservation principles, and sustainable tourism within a predictive heritage governance approach. The main contribution of this study lies in the development of the Heritage Remaining Useful Life (H_{RUL}) framework and its integration with digital twin systems, predictive maintenance concepts, and a human-in-the-loop decision-making structure for cultural heritage management. Although conceptually robust, the model remains theoretical and requires empirical validation and real-world implementation. Its applicability is influenced by data availability, infrastructural constraints, and institutional capacities, particularly in Small Data environments characteristic of cultural heritage systems.

Future research should focus on empirical testing through pilot studies and the development of scalable implementation strategies for sensor-

based and AI-supported heritage monitoring systems. Overall, the framework establishes a foundation for predictive, data-informed, and sustainability-oriented heritage governance.

References

1. Ashley-Smith, J. (1999). Risk assessment for object conservation. Routledge. <https://doi.org/10.4324/9780080938523>
2. Bruno, F., Bruno, S., De Sensi, G., Luchi, M. L., Mancuso, S., & Muzzupappa, M. (2010). From 3D reconstruction to virtual reality: A complete methodology for digital archaeological exhibition. *Journal of Cultural Heritage*, 11(1), 42–49. <https://doi.org/10.1016/j.culher.2009.02.006>
3. Bzdok, D., & Ioannidis, J. P. A. (2019). Exploration, inference, and prediction in neuroscience and biomedicine. *Trends in Cognitive Sciences*, 23(5), 427–440. <https://doi.org/10.1016/j.tics.2019.02.001>
4. Glaessgen, E. H., & Stargel, D. S. (2012). The digital twin paradigm for future NASA vehicles. In *53rd AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference and Co-located Conferences Online Proceedings* (p. 1818). <https://doi.org/10.2514/6.2012-1818>
5. Grieves, M. (2014). Digital twin: manufacturing excellence through virtual factory replication. *White paper*, 1(2014), 1-7. Florida Institute of Technology
6. Hochreiter, S., & Schmidhuber, J. (1997). Long short-term memory. *Neural Computation*, 9(8), 1735–1780. <https://doi.org/10.1162/neco.1997.9.8.1735>
7. ICOMOS. (1964). International Charter for the Conservation and Restoration of Monuments and Sites (The Venice Charter). https://www.icomos.org/images/DOCUMENTS/Charters/venice_e.pdf (17 February 2026)
8. LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*, 521(7553), 436–444. <https://doi.org/10.1038/nature14539>

9. Murphy, M., McGovern, E., & Pavia, S. (2009). Historic building information modelling (HBIM). *Structural Survey*, 27(4), 311–327. <https://doi.org/10.1108/02630800910985108>
10. Pan, S. J., & Yang, Q. (2010). A survey on transfer learning. *IEEE Transactions on Knowledge and Data Engineering*, 22(10), 1345–1359. <https://doi.org/10.1109/TKDE.2009.191>
11. Sikorska, J. Z., Hodkiewicz, M., & Ma, L. (2011). Prognostic modelling options for remaining useful life estimation. *Mechanical Systems and Signal Processing*, 25(5), 1803–1836. <https://doi.org/10.1016/j.ymssp.2010.11.018>
12. Tao, F., Zhang, H., Liu, A., & Nee, A. Y. C. (2018). Digital twin in industry: State-of-the-art. *IEEE Transactions on Industrial Informatics*, 15(4), 2405–2415. <https://doi.org/10.1109/TII.2018.2873186>
13. UNESCO World Heritage Centre. (2023). Operational Guidelines for the Implementation of the World Heritage Convention. <https://whc.unesco.org/en/guidelines/> (17 February 2026)